



WESTERLY

TYPHOON 37

SEPTEMBER 1990

STANDARD SPECIFICATION

HULL White GRP. Fin keel. Retrouse stern with 2 self draining lockers. Blue antifouling with red waterline stripe. Teak rubbing strake. Cathodic protection. Bronze seacocks and underwater fittings. Blue moulded coveline with red stripe under.

Hand laid in temperature and humidity controlled environment. 2 layers of isophthalic gelcoat and isophthalic resin in the first layer of mat plus biaxial combination and unidirectional reinforcement.

LLOYDS HULL CONSTRUCTION CERTIFICATE

RUDDER GRP with stainless steel 316 stock and framework.

KEEL Cast iron with stainless steel studs and twin locking nuts.

DECK/COCKPIT Grey moulded non-slip surface. Hatches in forward cabin, forward heads and saloon. Wheel steering (with rod links). Emergency tiller. Vented gas bottle stowage for 2 x 6 lb (2.7 kg) bottles. Compass on binnacle. Large cockpit locker. Anchor locker. Teak toe rail. Grey treadmaster on cockpit seats.

Hand laid isophthalic gelcoat with chopped strand mat biaxial combination and unidirectional reinforcement with layers of Fiset coremat.

DECK FITTINGS Stainless steel double rail pulpit and pushpit with stern gate. 24" (610mm) stanchions with double lifelines. 2-speed self-tailing winches (2 x foresheet, 2 x halyard). 2 winch handles. Spinnaker deck gear (excl pole and pole stowage). Twin bow roller. 2 bow, 2 stern and 2 spring cleats. 2 bow fairleads. Ensign staff socket. Teak handrails. Jammers for halyards, reefing lines and spinnaker gear (excl pole and pole stowage). Manual windlass. Twin headsail tracks (cars on outboard track).

SAILS AND RIGGING Fractional double spreader rig. Mainsail and No. 2 genoa (non-furling). Polyester main and jib halyards plus slab reefing and kicking strap all led aft in the coachroof. Topping lift and burgee halyard. Stainless steel standing rigging. Silver anodised boom and tapered mast. Twin groove headsail foil.

GENERAL EQUIPMENT Bilge pump. 35 lb plough anchor. 15 fathoms of 5/16" calibrated chain. 6 fenders. 2 x 40' mooring warps. 1 dry power fire extinguisher. 1 Gaz bottle.

ELECTRICAL SYSTEM Stern light. Bi-colour navigation light on pulpit. Steaming light. Deck light. 2 x 92 a/h (low maintenance) batteries. 12V switch panel with double pole circuit breakers and 5 spare circuits. 50 a/h alternator.

ENGINE Volvo 2003 (28 hp). 2-bladed propeller. Fresh water cooled. Sound insulation. Flexible mounting. Exhaust muffler.

TANKS 30 gallon fuel tank. Total water capacity 50 gallons in 2 tanks (stainless steel).

INTERIOR All woodwork in teak or teak faced ply. Upholstery available in a choice of fabrics.

FORWARD CABIN 2 single crossover bunks with an optional double berth conversion. Lockers and reading lights. Carpets.

FORWARD HEADS Marine WC. Hot and cold water supply to handbasin.

SALOON 2 fixed berths with lee cloths. Settee with double berth conversion. Table with bottle stowage and dust tray. Numerous lockers. Holly and Teak flooring. Reading and overhead lights with switch by hatchway. Wet locker.

NAVIGATION AREA Table with chart stowage and separate seat. Provision for books and instruments. White/red night light. Opening window. Chart light.

GALLEY Refrigerated drained ice box. 2 stainless steel sinks with hot and cold water supply. Rubbish bin. Gimbaled 2 burner cooker with oven and grill. Adequate stowage. Opening window. Marble style work surface with teak fiddle. Chopping board.

AFT HEADS Marine WC. Handbasin. Hot and cold water. Shower. Opening port to bridge deck.

AFT CABIN Double berth with wrap around settee. Hanging locker and opening port to bridge deck. Reading lights. Carpets.

TYPHOON 37

£

OPTIONS

DECK FITTINGS

- 187 Boarding ladder
- 508 Folding sprayhood

SAILS & RIGGING

- 350 Storm jib
- 1090 Tri-radial spinnaker (100%) 0.75oz
- 297 Spinnaker gear
- 310 Spinnaker pole and deck stowage
- 1684 Rotostay reefkit incl demountable drum and furling radial cut No.2 genoa and foam luff (in lieu of standard)
- 140 Tri-colour light and white masthead light

CLUB PACKAGE

- 1434 High Tech radial cut main (dual weight)
- 719 No.3 genoa (101%)
- 116 Sheet cars for coachroof tracks

NAVIGATIONAL EQUIPMENT

- 170 V-Tronix combined VHF aerial and Hawk indicator at masthead including co-ax to chart table, deck plugs and 12V supply
- 312 Nautech ST50 sounder
- 312 Nautech ST50 log
- 492 Nautech windspeed/direction main
- 244 Nautech multifunction repeater at chart table
- 2408 Autohelm 7000 for wheel or tiller steering

CABIN FITTINGS

- 210 Infill for double berth conversion in forecabin
- 236 Extra saloon hatch aft of mast

GENERAL

- 961 Cradle
- 503 Delivery to Gosport incl launch and commissioning

ALL PRICES ARE EX VAT

A full list of factory fitted extras and colour options is available on request